cedures Issue Date: 7 May 2004
erence No: Revision Date:
n Scheme 30 th July 2013
Revision No: 3
,

Australian Standard: Walking Tracks (AS 2156.1-2001)

The following table summarises specifications for the various elements of the *Australian Standard – Walking Tracks (AS-2156.1)*. It is provided here for comparative purposes, but note that (as explained previously) there is no direct correlation between the PWS and AS classes below class 3/T1 and the schemes are best used independently for different purposes. The PWS class 'Route' has no corresponding class in the AS scheme.

	1	2	3	4	5	6
Overview		High use, easy access, interpretation provided	Slightly modified environments, moderate numbers	0)		Often indistinct tracks in remote areas.
Terrain	No previous experience required.	No previous experience required.	No bushwalking experience required. May encounter steep slopes, water crossings, etc. Users responsible for own safety.	Users need to be self-reliant.	Users need to be self-reliant.	Users need to be self-reliant.
Width	>1.2m.	>900mm.	Generally <1.2m, variable.			
Surface & drainage	Broad, surfaced track suitable for wheelchairs.	Generally a modified or hardened surface.	Generally a modified surface, sections may be hardened.		Limited modification to natural surfaces. Alignment may be indistinct in places.	No modification of the natural environment.
	As per AS 1428; <1:14 (or 4° or 7%). Steps only with alternate ramp access.	Generally <1:10 (or 6° or 10%), minimal steps.	Generally <1:10 (or 6° or 10%), but may exceed 1:10 for short sections.	Limited to environmental and management considerations		May include steep sections of unmodified surfaces
	May include platforms, seats and barrier rails.	May include platforms, seats and barrier rails.	Generally only for specific safety and environmental considerations.	safety and environmental	Generally only for specific safety and environmental considerations.	Generally not provided
Signs	Frequent.	Frequent.			Limited, for management purposes.	Not provided
Weather	Not applicable	Not applicable	Severe weather may affect navigation and safety.	Severe weather may affect navigation and safety.		Severe weather may affect navigation and safety.
Risk management	Tracks and built facilities managed for public risk and inspected at 30 day intervals.	Tracks and built facilities managed for public risk and inspected at 3 month intervals.	Built facilities managed for public risk and inspected at 6 month intervals.	Built facilities managed for public risk and inspected at 6-12 month intervals.	,	Not be managed for public risk. Users responsible for personal safety.
Management intervention	High	Moderate to high	Moderate	Low to moderate	Low	Negligible
Publicity	Will normally appear on maps.	Will normally appear on maps.	Will normally appear on maps.	May be shown on maps	May be shown on maps	Will not be marked on maps

Department of Primary	PWS Track Classification Scheme Policy	Page 13 of 13
Industries, Parks, Water &	PWS P- 036	
Environment		